

- Power The World with Highest Efficiency

ENP-7025B

Features



- **250W Output, Active PFC**
- **Protections:** OVP, OPP, SCP, OTP
- **Reliability:** MTBF 100,000 hrs @ 25°C, Full Load
- **High Efficiency (80+ Bronze):** 83.56% @ 115Vac, Full Load
- **Safety Approval:** cUL, Nemko, CB, CCC, BSMI
- **Warranty:** 1-year manufacturer
- **Application:** Desktop PC, Industrial PC, Kiosk, Web Server



Input Specification					
Parameter	Conditions/Description	Min.	Normal	Max.	Units
Input Voltage Range	Universal Input	90	100-240	264	V(ac)
Input Frequency Range		47	60/50	63	Hz
Input Current	Measured at 90 Vac / 264 Vac input, full load output		8/4		A
Inrush Current	Measured at 45A@115Vrms /90A@ 230Vac (25°C ambient temperature, cold start).				A
Efficiency (80+ Bronze)	Measured at 115 Vac @ Full Load		83.56		%

Output Specification										
Parameter	Conditions/Description	Voltage Regulation			Ripple Noise	Output Current (Amps)				Units
		Range	Min. (V)	Max. (V)	(mVp-p)	Min.	Normal	Max.	Peak	
+3.3VDC		+/-5%	3.14	3.47	50	0.1	-	13	-	
+5VDC		+/-5%	4.75	5.25	50	0.2	-	14	-	
+12V1DC		+/-5%	11.4	12.6	120	0.6	-	18	20	
+12V2DC		+/-5%	11.4	12.6	120	0.6	-	18	20	
-12VDC		+/-10%	-10.8	-13.2	120	0	-	0.3	-	
+5VSB		+/-5%	4.75	5.25	50	0	-	2	2.5	
Voltage Hold-Up Time	Measured at 115Vac/47Hz or 230Vac/47Hz/100% load after power source removed.					17				mSec
Output Rise Time								10		mSec
Total Combined Output Load on +3.3V and +5V shall not exceed 80W .										
Total Combined Output of +12V1 & +12V2 can not exceed 240W .										

Environmental Specification					
Parameter	Conditions/Description	Min.	Normal	Max.	Units
MTBF	Calculated via MIL-HDBK-217F @ 25°C ambient temperature , Full load, 110 Vac	100,000			Hours
Operating Temperature	Full load	0		40	°C
Storage Temperature		-40		70	°C
Relative Humidity	Non-Condensing	20		85	%
Dimension	Length x Width x Height	150 x 81.5 x 40.5/5.9 x 3.2 x 1.6			mm / inch
Cooling Fan	12VDC	40 x 40 x 20			mm
ROHS	European Directive 2002/95/EC				

Reliability Protection		
Parameter	Conditions/Description	Recovery Mode
Overload	Transit to current limit mode if output over 110% - 150%	Shut Down Output, Auto recover once reset AC power-on by user
Over Voltage		Shut Down Output, Auto recover once reset AC power-on by user
Short Circuit		Shut Down Output, Auto Recover once faults conditions removed
Over Temperature		Shut Down Output, Auto Recover once faults conditions removed

Safety & EMC Compliance		
Category	Standard	Comment
SAFETY	cUL, Nemko, CB, CCC, BSMI	Approved
EMI Conduction & Radiation		Compliance
Harmonic Current Emissions		Compliance
EMS Immunity	Voltage Fluctuation	EN61000-3-2
	Electrostatic Discharge (ESD)	EN61000-3-3
	Radiated Susceptibility	EN61000-4-2
	Fast Transients / Burst - EFT	EN61000-4-3
	Input Line Surge Immunity	EN61000-4-4
	Conducted Susceptibility	EN61000-4-5
	Power Frequency Magnetic Field	EN61000-4-6
Voltage Dips	EN61000-4-8	
		EN61000-4-11

