

# RAP1224-M

## 300W



### Features

- Remote Access Control for Resetting Power.
- Reduce Service Cost and Power Adapter Cost.
- Free up Space and Eliminate Heat Generation.
- Universal AC Input Voltage Auto-Sensing.
- Active PFC (Power Factor Correction).
- Short circuit, Over Current, and Voltage Protection.

### Technical Specifications

Dimension (W x L x H)		277mm x 314mm x 43mm (10.9" x 12.36" x 1.7")	
AC Input	Voltage	100V~240V (Auto Sensing)	
	Frequency	50Hz~60Hz	
	Input Current	10A@100V	10A@240V
	Surge Current	15A@100V	35A@240V
	Leakage Current	0.35A@100V	0.5A@240V
	Power Factor	0.99@100V	0.92@240V
AC Output		100V~240V / 6A / 50Hz~60Hz	
DC Output	USB	0A~2A (Each Port 0.5A)	
	5V	0A~3A	
	6V / 9V	0A~3A / 0A~2A (0W~18W)	
	12V	0A~8A	
	24V	0A~6.3A	
DC Regulation		-5% ~ +5%	
Efficiency	12VDC	81%@100VAC	83%@240VAC
	24VDC	82%@100VAC	84%@240VAC
Communication Interface		56Kbps Internal Modem	
Operating Environment	Temperature	-10°C ~ +60°C	
	Humidity	10% ~ 95% 😊	
Storage Environment	Temperature	-30°C ~ +75°C	
	Humidity	10% ~ 95%	
Safeties Approval		UL (Level 3), CB, TUV, FCC (Class B), CE	

# 12/24 VDC